

P/N NAS6208-28

Description

Fastener Length: 2-9/32", Thread: 1/2-20, Thread Length: 35/64", NAS6208 series bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS620828

Minimum Qty (MOQ):

NSN: 5306-01-114-5143

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6208-28 Specifications

Thread Direction: Right-hand Thread Length: 0.503 Inches Minimum And 0.553 Inches Maximum Fastner Length: 2.263 Inches Minimum And 2.293 Inches Maximum Head Style: Dished Hexagon Head Height: 0.250 Inches Minimum And 0.265 Inches Maximum Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Grip Diameter: 0.4985 Inches Minimum And 0.4995 Inches Maximum Nominal Thread Diameter: 0.500 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mili-s-5000 Mil Spec 1st Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Mili-s-6049 Mili S		
Thread Length: 5.203 Inches Minimum And 0.553 Inches Maximum Fastener Length: 2.263 Inches Minimum And 2.293 Inches Maximum Head Style: Dished Hexagon 0.250 Inches Minimum And 0.265 Inches Maximum Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Grip Diameter: 0.4985 Inches Minimum And 0.752 Inches Maximum Grip Diameter: 0.500 Inches Minimum And 0.4995 Inches Maximum Nominal Thread Diameter: 0.500 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 40.6000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: 5teel Comp E4340 Overall Or Steel Comp 8740 Overall Miles-5000 Mil Spec 1st Material Response Overall Or Miles-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Thread Class:	3a
Fastener Length: 2.263 Inches Minimum And 2.293 Inches Maximum Head Style: Dished Hexagon Head Height: 0.250 Inches Minimum And 0.265 Inches Maximum Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Grip Dlameter: 0.4985 Inches Minimum And 0.4995 Inches Maximum O.500 Inches Minimum And 0.4995 Inches Maximum Nominal Thread Diameter: 0.500 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Q-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Thread Direction:	Right-hand
Head Style: Dished Hexagon Head Height: 0.250 Inches Minimum And 0.265 Inches Maximum Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Grip Diameter: 0.4985 Inches Minimum And 0.4995 Inches Maximum Nominal Thread Diameter: 0.500 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Thread Length:	0.503 Inches Minimum And 0.553 Inches Maximum
Head Height: 0.250 Inches Minimum And 0.265 Inches Maximum Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Orip Diameter: 0.4985 Inches Minimum And 0.4995 Inches Maximum Nominal Thread Diameter: 0.500 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Wils-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Cadmium Overall And Chromate Overall Cadmium Overall And Chromate Overall Cadmium Overall And Chromate Overall Thread Series Designator: Unif	Fastener Length:	2.263 Inches Minimum And 2.293 Inches Maximum
Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Grip Diameter: 0.4985 Inches Minimum And 0.4995 Inches Maximum Nominal Thread Diameter: 0.500 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unjf	Head Style:	Dished Hexagon
Grip Diameter: 0.4985 Inches Minimum And 0.4995 Inches Maximum 0.500 Inches 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Material Response Overall Or Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall And Chromate Overall Surface Treatment Document And Classification: Cadmium Overall And Chromate Overall Oq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Head Height:	0.250 Inches Minimum And 0.265 Inches Maximum
Nominal Thread Diameter: Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Thread Series Designator: Unjf	Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Length:1.740 Inches Minimum And 1.760 Inches MaximumThread Quantity Per Inch:20Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn StdSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Grip Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: 5teel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Nominal Thread Diameter:	0.500 Inches
Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Threads Material: 32.0 Microinches Threads Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: 32.0 Microinches Threads Alil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Additional Chromate Overall 32.0 Microinches Grip 3	Grip Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Cadmium Overall And Chromate Overall Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Thread Quantity Per Inch:	20
Surface Finish: Surface Finish: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish: Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish: Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material: Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Surface Finish:	32.0 Microinches Grip
Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Unjf Unjf	Surface Finish:	32.0 Microinches Threads
Surface Treatment And Classification: Surface Treatment Document And Classification: Clas	Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And Classification: Classification: Unjf Unjf	Material Document And Classification:	
Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas6208 Professional/industrial Association Standard	Thread Series Designator:	Unjf
	Specification/standard Data:	80205-nas6208 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6208-28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6208-28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6208-28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6208-28 and selecting the quantity you want then