

Description

NAS6208-44D Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS620844D
Minimum Qty (MOQ):	2
NSN:	5306-01-142-2133
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS6208-44D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.520 Inches Nominal
Fastener Length:	3.278 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.257 Inches Nominal
Width Between Flats:	0.746 Inches Nominal
Grip Diameter:	0.4990 Inches Nominal
Shank Unthreaded Hole Diameter:	0.177 Inches Nominal First Hole
Nominal Thread Diameter:	0.500 Inches
Grip Length:	2.750 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	3.080 Inches Nominal First Hole
Material:	Steel Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6208 Professional/Industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6208-44D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.