

**Description**

Fastener Length: 5-17/32", Thread: 1/2-20, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS620880
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-522-6119
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS6208-80 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.528 Inches Nominal
<b>Fastener Length:</b>	5.513 Inches Minimum And 5.543 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.250 Inches Minimum And 0.265 Inches Maximum
<b>Width Between Flats:</b>	0.741 Inches Minimum And 0.752 Inches Maximum
<b>Grip Diameter:</b>	0.4979 Inches Minimum And 0.4985 Inches Maximum
<b>End Item Identification:</b>	Wash Plate
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Grip Length:</b>	4.990 Inches Minimum And 5.010 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4340 Overall And Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Ams 6322 Assn Std All Material Responses Overall Or Ams 6415 Assn Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type 2. Class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205 - Nas-6208 Professional/Industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6208-80> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.