

Description

Fastener Length: 5-9/16", Thread: 1/2-20, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS620882
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-521-2038
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS6208-82 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.528 Inches Nominal
Fastener Length:	5.563 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.250 Inches Minimum And 0.265 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.498 Inches Minimum And 0.499 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	5.125 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Ams 6415 Assn Std 1st Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Tyii, Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6208 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6208-82> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.