

Description

Fastener Length: 5-9/16", Thread: 1/2-20, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS620882 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-521-2038 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |



P/N NAS6208-82 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.528 Inches Nominal |
| Fastener Length: | 5.563 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.250 Inches Minimum And 0.265 Inches Maximum |
| Width Between Flats: | 0.741 Inches Minimum And 0.752 Inches Maximum |
| Grip Diameter: | 0.498 Inches Minimum And 0.499 Inches Maximum |
| Nominal Thread Diameter: | 0.500 Inches |
| Grip Length: | 5.125 Inches Nominal |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Ams 6415 Assn Std 1st Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Tyii, Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6208 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6208-82> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.