

P/N NAS6209-103D

Description

Fastener Length: 7-41/64", Thread: 1/2-18, Thread Length: 1-13/64"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS6209103D

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-300-2928

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6209-103D Specifications

Thread Direction: Right-hand Thread Length: 1.163 Inches Minimum And 1.213 Inches Maximum Fastener Length: 7.611 Inches Minimum And 7.641 Inches Maximum Head Style: Dished Hexagon Head Height: 0.281 Inches Minimum And 0.296 Inches Maximum Width Between Flats: 0.865 Inches Minimum And 0.877 Inches Maximum Width Between Flats: 0.865 Inches Minimum And 0.877 Inches Maximum Grip Diameter: 0.5605 Inches Minimum And 0.877 Inches Maximum Shank Unthreaded Hole Diameter: 0.5605 Inches Minimum First Hole And 0.151 Inches Maximum First Hole Nominal Thread Diameter: 0.5602 Inches Minimum First Hole And 0.151 Inches Maximum First Hole Nominal Thread Diameter: 0.5602 Inches Minimum And 6.448 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Bullardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 3.20 Microinches Bearing Surface Of Head Surface Finish: 3.2.0 Microinches Bearing Surface Of Head Surface Finish: 3.2.0 Microinches Grip Surface Finish: 3.2.0 Microinches Grip Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf		
Thread Length: 1.63 Inches Minimum And 1.213 Inches Maximum Fastener Length: 7.611 Inches Minimum And 7.641 Inches Maximum Head Style: Dished Haxagon Width Between Flats: 0.281 Inches Minimum And 0.296 Inches Maximum Width Between Flats: 0.5605 Inches Minimum And 0.877 Inches Maximum Grip Diameter: 0.5605 Inches Minimum And 0.5615 Inches Maximum Shank Unthreaded Hole Diameter: 0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole Nominal Thread Diameter: 0.562 Inches Grip Length: 0.6428 Inches Minimum And 6.448 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 37.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Material: 32.0 Microinches Threads Material: 32.0 Microinches Threads Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Unjf Whead Series Designator: Unjf	Thread Class:	3a
Fastener Length: 7.611 Inches Minimum And 7.641 Inches Maximum Dished Hexagon Head Style: 0.281 Inches Minimum And 0.296 Inches Maximum Width Between Flats: 0.865 Inches Minimum And 0.877 Inches Maximum Grip Diameter: 0.5605 Inches Minimum And 0.877 Inches Maximum Shank Unthreaded Hole Diameter: 0.5605 Inches Minimum And 0.5615 Inches Maximum Shank Unthreaded Hole Diameter: 0.562 Inches Minimum First Hole And 0.151 Inches Maximum First Hole Nominal Thread Diameter: 0.562 Inches Grip Length: 6.428 Inches Minimum And 6.448 Inches Maximum Inthread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 160000 Pounds Per Square Inch Hardness Rating: 160000 Pounds Per Square Inch Hardness Rating: 17.394 Inches Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Miles-S000 Mil Spec 1st Material Response Overall Or Miles-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Miles-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Miles-6049 Miles-6	Thread Direction:	Right-hand
Head Style: Head Height: 0.281 Inches Minimum And 0.296 Inches Maximum 0.865 Inches Minimum And 0.877 Inches Maximum 0.5605 Inches Minimum And 0.877 Inches Maximum 0.5605 Inches Minimum And 0.5615 Inches Maximum 0.5605 Inches Minimum And 0.5615 Inches Maximum 0.5610 Inches Minimum First Hole And 0.151 Inches Maximum First Hole Nominal Thread Diameter: 0.562 Inches Grip Length: 0.562 Inches Minimum And 6.448 Inches Maximum First Hole Nominal Thread Diameter: 0.562 Inches Minimum And 6.448 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 0514ance From Head Largest Bearing Surface To Shank Hole Center: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 7.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material Document And Classification: Mili-s-5000 Mil Spec 1st Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Thread Length:	1.163 Inches Minimum And 1.213 Inches Maximum
Head Height: 0.281 Inches Minimum And 0.296 Inches Maximum Width Between Flats: 0.865 Inches Minimum And 0.877 Inches Maximum Grip Diameter: 0.5605 Inches Minimum And 0.5615 Inches Maximum Shank Unthreaded Hole Diameter: 0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole Nominal Thread Diameter: 0.562 Inches Grip Length: 6.428 Inches Minimum And 6.448 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Fastener Length:	7.611 Inches Minimum And 7.641 Inches Maximum
Width Between Flats: O.865 Inches Minimum And 0.877 Inches Maximum O.5605 Inches Minimum And 0.5615 Inches Maximum Shank Unthreaded Hole Diameter: O.560 Inches Minimum First Hole And 0.151 Inches Maximum First Hole Nominal Thread Diameter: O.562 Inches Grip Length: 6.428 Inches Minimum And 6.448 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 7.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole And 7.444 Inches Maximum First Hole Surface From Head Largest Bearing Surface To Shank Hole Center: Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Head Style:	Dished Hexagon
Grip Diameter: 0.5605 Inches Minimum And 0.5615 Inches Maximum 0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole Nominal Thread Diameter: 0.562 Inches Grip Length: 6.428 Inches Minimum And 6.448 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch 17.394 Inches Minimum First Hole And 7.444 Inches Maximum Overall 17.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole 18 18 18 18 18 18 18 18 18 1	Head Height:	0.281 Inches Minimum And 0.296 Inches Maximum
Shank Unthreaded Hole Diameter: O.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole Nominal Thread Diameter: O.562 Inches Grip Length: 6.428 Inches Minimum And 6.448 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: Oistance From Head Largest Bearing Surface To Shank Hole Center: Surface Finish: Surface Finish: Surface Finish: Surface Finish: Surface Finish: Surface Finish: Material: Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Furface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Width Between Flats:	0.865 Inches Minimum And 0.877 Inches Maximum
Nominal Thread Diameter: Grip Length: 6.428 Inches Minimum And 6.448 Inches Maximum Thread Quantity Per Inch: 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Unjf	Grip Diameter:	0.5605 Inches Minimum And 0.5615 Inches Maximum
Grip Length: 6.428 Inches Minimum And 6.448 Inches Maximum 18 Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 5. Juriace Finish: 6.428 Inches Minimum And 6.448 Inches Maximum 6.448 Inches Minimum Overall 7. 394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole 8. Juriace Finish: 9. Juriace Finish: 9	Shank Unthreaded Hole Diameter:	0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 7.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole 8.000 Microinches Bearing Surface Of Head 8.000 Microinches Bearing Surface Of Head 8.000 Microinches Grip 8.000 Microinches Threads 8.000 Microinches Threads 8.000 Microinches Threads 8.000 Microinches Threads 8.000 Mill Spec 1st Material Response Overall Or Mill-s-6049 Mill Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall 8.000 Mill Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.562 Inches
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 7.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole 82.0 Microinches Bearing Surface Of Head 83.0 Microinches Grip 83.0 Microinches Grip 83.0 Microinches Threads 84.0 Microinches Threads 85.0 Microinches Threads 85.0 Microinches Threads 86.0 Rockwell C Minimum First Hole 86.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 86.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 86.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 87.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole 88.0 Microinches Bearing Surface Of Head 89.0 Microinches Grip 99.0 Microinches Bearing Surface Of Head 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 99.0 Microinches Maximum First Hole 99.0 Microinches Maximum First H	Grip Length:	6.428 Inches Minimum And 6.448 Inches Maximum
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 7.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole 82.0 Microinches Bearing Surface Of Head 83.0 Microinches Grip 83.0 Microinches Grip 83.0 Microinches Threads 84.0 Microinches Threads 85.0 Microinches Threads 86.0 Rockwell C Minimum First Hole And 7.444 Inches Maximum First Hole 86.0 Rockwell C Minimum Overall And 7.444 Inches Maximum First Hole 87.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole 88.0 Microinches Bearing Surface Of Head 89.0 Microinches Grip 89.0 Microinches Grip 89.0 Microinches Threads 89.0 Microinches Grip 89.0 Microinches Bearing Surface Of Head 89.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 89.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 89.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 89.0 Microinches Bearing Surface Of Head 89.0 Microinches Bearing Surface Of Head 89.0 Microinches Bearing Surface Of Head 89.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 89.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 89.0 Microinches Bearing Surface Of Head 89.0 Microinches Grip 89.0 Microinches Maximum First Hole 89.0 Microinches Maximum First Hole 89.0 Microinches Grip 89.0 Microinches Grip 89.0 Microinches Grip 89.0 Microinches Maximum First Hole 89.0 Microinches Maximu	Thread Quantity Per Inch:	18
Distance From Head Largest Bearing Surface To Shank Hole Center: Surface Finish: Material: Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unjf Oq.p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Thread Series Designator: 7.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole 7.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole 7.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole 82.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 32.0 Microinches Maximum First Hole And 7.444 Inches Maximum First Hole 4.444 Inches Maximum First Hole	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Center: 7.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish: Surface Finish: Surface Finish: Material: Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Unjf Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Cadmium Overall And Chromate Overall Unjf	Distance From Head Largest Bearing Surface To Shank Hole Center:	7.394 Inches Minimum First Hole And 7.444 Inches Maximum First Hole
Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material: Material Document And Classification: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Surface Finish:	32.0 Microinches Grip
Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Unjf	Surface Finish:	32.0 Microinches Threads
Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Material Document And Classification:	
Thread Series Designator: Unjf	Surface Treatment:	Cadmium Overall And Chromate Overall
·	Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas6209 Professional/industrial Association Standard	Thread Series Designator:	Unjf
	Specification/standard Data:	80205-nas6209 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6209-103D</u> and selecting the quantity you want then click 'add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.
Provided by <u>Military-Fasteners.com</u>