

Description

Fastener Length: 2-3/8", Thread: 1/2-18, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS620929D |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-482-2245 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N NAS6209-29D Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.594 Inches Nominal |
| Fastener Length: | 2.406 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.281 Inches Minimum And 0.296 Inches Maximum |
| Width Between Flats: | 0.865 Inches Minimum And 0.877 Inches Maximum |
| Grip Diameter: | 0.560 Inches Minimum And 0.561 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.562 Inches |
| Grip Length: | 1.812 Inches Nominal |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 2.174 Inches Minimum First Hole And 2.224 Inches Maximum First Hole |
| Material: | Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Ams6415 Assn Std 1st Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Tyii, Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6209-29D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.