

Description

Fastener Length: 2-47/64", Thread: 1/2-18, Thread Length: 19/32",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS620934 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5306-01-367-9273 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6209-34 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.594 Inches Nominal |
| Fastener Length: | 2.704 Inches Minimum And 2.734 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.281 Inches Minimum And 0.296 Inches Maximum |
| Width Between Flats: | 0.865 Inches Minimum And 0.877 Inches Maximum |
| Locking Feature: | Patch Locking Feature Or Pellet Locking Feature Or Strip Locking Feature |
| Grip Diameter: | 0.5605 Inches Minimum And 0.5615 Inches Maximum |
| Nominal Thread Diameter: | 0.562 Inches |
| Grip Length: | 2.115 Inches Minimum And 2.135 Inches Maximum |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4340 Overall Or Steel Comp 8740 Overallplastic Polyamide Locking Featuresteel Comp 4340 Fastener Or Steel Comp 8740 Fastener |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overallmil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener |
| Surface Treatment: | Cadmium Overall And Chromate Overallcadmium Fastener And Chromate Fastener |
| Surface Treatment Document And Classification: | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overallqq-p-416,ty2,cl2 Fed Spec Single Treatment Response Fastener |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6209 Professional/industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6209-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.