


**Description**

Fastener Length: 4-39/64", Thread: 1/2-18, Thread Length: 19/32

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS620964
Minimum Qty (MOQ):	1
NSN:	5306-01-445-7829
Schedule B:	7318.15.8085
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS6209-64 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.594 Inches Nominal
<b>Fastener Length:</b>	4.579 Inches Minimum And 4.609 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.281 Inches Minimum And 0.296 Inches Maximum
<b>Width Between Flats:</b>	0.865 Inches Minimum And 0.877 Inches Maximum
<b>Grip Diameter:</b>	0.5599 Inches Minimum And 0.5605 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.562 Inches
<b>Grip Length:</b>	3.990 Inches Minimum And 4.010 Inches Maximum
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mils-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type 2, Class 2 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6209 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6209-64> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.