

**Description**

Hole diameter: 0.143", overall diameter: 0.267", thickness .016, aluminum alloy, NAS620 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS620A6L
Minimum Qty (MOQ):	100
NSN:	5310-00-616-8118
Schedule B:	7616.10.8000
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



\* See page 2 for technical characteristics

## P/N NAS620A6L Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Hole Diameter:</b>	0.151 Inches Minimum And 0.161 Inches Maximum
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Center Hole Shape Style:</b>	Round
<b>Thickness:</b>	0.016 Inches Nominal
<b>Overall Diameter:</b>	0.262 Inches Minimum And 0.282 Inches Maximum
<b>End Item Identification:</b>	Aircraft, Airlifter C-17a;missile, Tomahawk;aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130);helicopter, Mh-53e;missile, Air-to-ground, Hellfire;torpedo, Adcap 48;missile, All-weather Anti-ship, Harpoon (agm-84);aircraft, C-2a (reprocured);radio Terminal Set, An/srq-4;aircraft, Eagle F-15
<b>Material:</b>	Aluminum Alloy 5052 Overall
<b>Material Document And Classification:</b>	Qq-a-250/8 Fed Spec Single Material Response Overall

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS620A6L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.