

Description

Diameter: 0.086, thickness .016, size: #2, corrosion resistant, stainless steel, passivated, NAS620 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[NAS620-C2](#)

SKU / Model:	NAS620C2
Minimum Qty (MOQ):	100
NSN:	5310-00-043-4708
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N NAS620C2 Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.079 Inches Minimum And 0.099 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.016 Inches Nominal
Overall Diameter:	0.144 Inches Minimum And 0.164 Inches Maximum
End Item Identification:	W/s:countermeasure Set, An/slq-32; Tactical Data System. An/uva-4 (v); Missile, Advanced Medium Range Air-to-air (amraam)/aim120a; Repair Facility, 0a8991; Sentinel Radar System; Support Equipment, B-1 Aircraft; Teammate, An/trq-32; Test Station, Oq-290(v)msm; Support Equipment, B-52 Aircraft; Communications Terminal, Satellite An/gsc-39(v)1
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Specification/standard Data:	80205-nas620 Professional/industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS620C2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.