

Description

diameter: 0.099, thickness .016, corrosion resistant, passivated, NAS620 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[NAS620-C3L](#)

SKU / Model:	NAS620C3L
Minimum Qty (MOQ):	100
NSN:	5310-00-970-4841
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N NAS620C3L Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.102 Inches Minimum And 0.112 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.016 Inches Nominal
Overall Diameter:	0.175 Inches Minimum And 0.195 Inches Maximum
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 304l Overall Or Steel Comp 305 Overall Or Steel Comp 309 Overall Or Steel Comp 310 Overall Or Steel Comp 316 Overall Or Steel Comp 316l Overall Or Steel Comp 321 Overall Or Steel Comp 323 Overall Or Steel Comp 347 Overall Or Steel Comp 348 Overall
Material Document And Classification:	Qq-s-766 Fed Spec All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas 620 Professional/industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS620C3L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.