

Description

Fastener Length: 1-37/64", Thread: 5/8-32, Thread Length: 5/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS621015 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-334-7903 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS6210-15 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.626 Inches Nominal |
| Fastener Length: | 1.549 Inches Minimum And 1.579 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.312 Inches Minimum And 0.327 Inches Maximum |
| Width Between Flats: | 0.934 Inches Nominal |
| Grip Diameter: | 0.6230 Inches Minimum And 0.6240 Inches Maximum |
| End Item Identification: | Pacer Dawn |
| Nominal Thread Diameter: | 0.6250 Inches |
| Grip Length: | 0.928 Inches Minimum And 0.948 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS6210-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.