

P/N NAS6210-24D

Description

Fastener Length: 2-9/64", Thread: 5/8-18, Thread Length: 41/64", NAS6210 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS621024D

Minimum Qty (MOQ):

NSN: 5306-01-209-7162

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6210-24D Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.601 Inches Minimum And 0.651 Inches Maximum |
| Fastener Length: | 2.111 Inches Minimum And 2.141 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.312 Inches Minimum And 0.327 Inches Maximum |
| Width Between Flats: | 0.928 Inches Minimum And 0.940 Inches Maximum |
| Grip Diameter: | 0.6230 Inches Minimum And 0.6240 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.141 Inches Minimum And 0.151 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.625 Inches |
| Grip Length: | 1.490 Inches Minimum And 1.510 Inches Maximum |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum Overall |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.944 Inches Minimum And 1.994 Inches Maximum First Hole |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp E4340 Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Fed Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6210 Professional/industrial Association Standard |
| | |

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS6210-24D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.