

**Description**

Fastener Length: 2-33/64", Thread: 5/8-18, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS621030D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-218-3987
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS6210-30D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.626 Inches Nominal
<b>Fastener Length:</b>	2.486 Inches Minimum And 2.516 Inches Maximum
<b>Head Style:</b>	Undercut Hexagon
<b>Head Height:</b>	0.312 Inches Minimum And 0.327 Inches Maximum
<b>Width Between Flats:</b>	0.928 Inches Minimum And 0.940 Inches Maximum
<b>Grip Diameter:</b>	0.6230 Inches Minimum And 0.6240 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.141 Inches Minimum And 0.151 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.625 Inches
<b>Grip Length:</b>	1.865 Inches Minimum And 1.885 Inches Maximum
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	2.274 Inches Minimum And 2.314 Inches Maximum First Hole
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6210 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS6210-30D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.