

Description

Fastener Length: 2-33/64", Thread: 5/8-18, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS621030D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-218-3987
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS6210-30D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.626 Inches Nominal
Fastener Length:	2.486 Inches Minimum And 2.516 Inches Maximum
Head Style:	Undercut Hexagon
Head Height:	0.312 Inches Minimum And 0.327 Inches Maximum
Width Between Flats:	0.928 Inches Minimum And 0.940 Inches Maximum
Grip Diameter:	0.6230 Inches Minimum And 0.6240 Inches Maximum
Shank Unthreaded Hole Diameter:	0.141 Inches Minimum And 0.151 Inches Maximum First Hole
Nominal Thread Diameter:	0.625 Inches
Grip Length:	1.865 Inches Minimum And 1.885 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.274 Inches Minimum And 2.314 Inches Maximum First Hole
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6210 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS6210-30D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.