

P/N NAS6210-96D

Description

Fastener Length: 6-39/64", Thread: 5/8-18, Thread Length: 5/8", NAS6210 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS621096D

Minimum Qty (MOQ):

NSN: 5306-01-247-3502

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6210-96D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.626 Inches Nominal
Fastener Length:	6.410 Inches Minimum And 6.611 Inches Maximum
Head Style:	Hexagon
Head Height:	0.312 Inches Minimum And 0.327 Inches Maximum
Width Between Flats:	1.050 Inches Nominal
Grip Diameter:	0.6120 Inches Minimum And 0.6150 Inches Maximum
Nominal Thread Diameter:	0.625 Inches
Grip Length:	5.990 Inches Minimum And 6.010 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Minimum Yield Strength:	160000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-c-320,cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6210-96d Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS6210-96D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS6210-96D and selecting the