



Military-Fasteners.com

P/N NAS6216-40

Description

Fastener Length: 3-13/32", Thread: 1--12, Thread Length: 57/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS621640
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-494-9383
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6216-40 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.895 Inches Nominal
Fastener Length:	3.380 Inches Minimum And 3.410 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.500 Inches Minimum And 0.515 Inches Maximum
Width Between Flats:	1.427 Inches Minimum And 1.440 Inches Maximum
Grip Diameter:	0.9980 Inches Minimum And 0.9990 Inches Maximum
End Item Identification:	B-52 Aircraft
Nominal Thread Diameter:	1.000 Inches
Grip Length:	2.490 Inches Minimum And 2.510 Inches Maximum
Thread Quantity Per Inch:	12
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4140 Overall
Material Document And Classification:	Ams 6349 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Typeii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	81205-nas6216 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6216-40> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.