

P/N NAS623-2-16

Military-Fasteners.com

#### Description

Fastener Length: 1-9/32", Thread: 8-32, Thread Length: 19/64

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS623216
Minimum Qty (MOQ):	50
NSN:	5305-00-144-1438
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS623-2-16 Specifications

Thread Direction:Right-handThread Length:0.251 Inches Minimum And 0.301 Inches MaximumFastener Length:1.261 Inches Minimum And 0.301 Inches MaximumHead Style:Pan No. 2Head Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.322 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.106 Inches Minimum And 0.115 Inches MaximumThread Quantity Per Inch:32Screw Material Strength:160000 Pounds Per Square InchScrew Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Pocument And Classification:Qn-p-416 Type 2 Cl 2 Fed Spec Single Treatment ResponseThread Series Designator:Unjc		
Thread Length:0.51 Inches Minimu And 0.301 Inches MaximumFastener Length:1.261 Inches Minimu And 1.291 Inches MaximumHead Style:Pan No. 2Head Diameter:0.306 Inches Minimu And 0.322 Inches MaximumInternal Drive Style:0.105 Inches Minimu And 0.115 Inches MaximumNominal Thread Diameter:0.106 Inches Minimu And 0.115 Inches MaximumNominal Thread Diameter:0.164 Inches0.164 Inches32Minimum Tensile Strength:160000 Pounds Per Square InchBarcew Material:Sco Rockwell C Minimu And 40.0 Rockwell C MaximumScrew Material:Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740Screw Surface Treatment:Cadmium And ChromateScrew Surface Treatment:Cadmium And ChromateStrew Surface Treatment:Cadmium And ChromateStrew Surface Treatment:DingUnicUnic	Thread Class:	2a
Fastener Length:1.261 Inches Minimum And 1.291 Inches MaximumHead Style:Pan No. 2Head Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 InchesInternal Drive Style:Scoress Type 1Nominal Thread Diameter:0.164 InchesBinimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew MaterialSteel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740Screw Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rdScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document And Classification:Qu-p-416 Ty 2 Cl 2 Fed Spec Single Treatment ResponseThread Series Designator:Unjc	Thread Direction:	Right-hand
Head Style:Pan No. 2Head Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 InchesThread Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:6.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Stel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740Screw Material Document And Classification:Odimium And ChromateScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment:Ordp: -p.416 Type Classification:UnjcUnjc	Thread Length:	0.251 Inches Minimum And 0.301 Inches Maximum
Head Diameter:0.306 Inches Minimum And 0.322 Inches MaximumHead Height:0.105 Inches Minimum And 0.115 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 InchesOnde Internal Drive Style:0.164 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740Screw Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document And Classification:Qu-p-416 Ty 2 Cl 2 Fed Spec Single Treatment ResponseThread Series Designator:Unjc	Fastener Length:	1.261 Inches Minimum And 1.291 Inches Maximum
Head Height:0.105 Inches Minimum And 0.115 Inches MaximumInternal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 Inches232Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740Screw Material Document And Classification:Gadmium And ChromateScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document And Classification:Q-p-416 Ty 2 Cl 2 Fed Spec Single Treatment ResponseThread Series Designator:Unjc	Head Style:	Pan No. 2
Internal Drive Style:Cross Recess Type 1Nominal Thread Diameter:0.164 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740Screw Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document And Classification:Qu-p-416 Ty 2 Cl 2 Fed Spec Single Treatment ResponseThread Series Designator:Unjc	Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Nominal Thread Diameter:0.164 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740Screw Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment ResponseThread Series Designator:Unjc	Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Thread Quantity Per Inch:32Minimum Tensile Strength:60000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740Screw Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rdScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document AndQu-p-416 Type Cla Spec Single Treatment ResponseDigUnjc	Internal Drive Style:	Cross Recess Type 1
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740Screw Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment ResponseUnjc	Nominal Thread Diameter:	0.164 Inches
Hardness Rating:36.0 Rockwell C Minimum And 40.0 Rockwell C MaximumScrew Material:Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740Screw Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment ResponseMiread Series Designator:Unjc	Thread Quantity Per Inch:	32
Screw Material:Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740Screw Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment ResponseMiterial ResponseUnic	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material ResponseScrew Surface Treatment:Cadmium And ChromateScrew Surface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment ResponseThread Series Designator:Unjc	Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material Document And Classification:   Material Response     Screw Surface Treatment:   Cadmium And Chromate     Screw Surface Treatment Document And   Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response     Thread Series Designator:   Unjc	Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740
Screw Surface Treatment Document And Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response   Classification: Unjc	Screw Material Document And Classification:	
Classification:   Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response     Thread Series Designator:   Unjc	Screw Surface Treatment:	Cadmium And Chromate
	Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response
Specification/standard Data: 80205-nas623 Professional/industrial Association Standard	Thread Series Designator:	Unjc
	Specification/standard Data:	80205-nas623 Professional/industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS623-2-16</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.