

Description


Fastener Length: 1-1/2", Thread: 8-32, Thread Length: 1/4", NAS623 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS623220
Minimum Qty (MOQ):	50
NSN:	5305-01-103-1154
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS623-2-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Nominal
Fastener Length:	1.526 Inches Nominal
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Or Mil-s-5000 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty li Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas623 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS623-2-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.