

P/N NAS623-2-34

Military-Fasteners.com

Description

NAS623-2-34 Machine Screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS623234
Minimum Qty (MOQ):	5
NSN:	5305-00-962-5706
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS623-2-34 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.189 Inches Minimum And 0.301 Inches Maximum
Fastener Length:	2.386 Inches Minimum And 2.416 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS623-2-34</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.