

P/N NAS623-2-4

Description

length: 0.526", grip: 0.250", thread: 8-32, pan head machine screw, short thread, philips recess, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS62324

Minimum Qty (MOQ): 100

NSN: 5305-00-688-1422

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS623-2-4 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.189 Inches Minimum And 0.301 Inches Maximum
Fastener Length:	0.511 Inches Minimum And 0.541 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams6300 Assn Std 6th Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS623-2-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.