

**Description**


length: 0.588", grip: 0.312", thread: 8-32, pan head, short thread, philips recess, cadmium plated alloy steel, NAS623 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS62325
Minimum Qty (MOQ):	100
NSN:	5305-01-332-5362
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS623-2-5 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.276 Inches Nominal
<b>Fastener Length:</b>	0.573 Inches Minimum And 0.603 Inches Maximum
<b>Head Style:</b>	Modified Pan
<b>Head Diameter:</b>	0.306 Inches Minimum And 0.322 Inches Maximum
<b>Head Height:</b>	0.105 Inches Minimum And 0.115 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type li
<b>Nominal Thread Diameter:</b>	0.1640 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Screw Material:</b>	Steel Comp 4140
<b>Screw Material Document And Classification:</b>	Mil-s-5626 Mil Std Single Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty li,cl 2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas623-2-5 Professional/industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS623-2-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.