



★ FASTENERS

Military-Fasteners.com

P/N NAS623-3-11

Description

length: 0.964", grip: 0.688", thread: 10-32, pan head, short thread, philips recess, cadmium plated alloy steel, NAS623 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS623311
Minimum Qty (MOQ):	100
NSN:	5305-00-061-3156
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS623-3-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.251 Inches Minimum And 0.301 Inches Maximum
Fastener Length:	0.949 Inches Minimum And 0.979 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp E4340 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 6150 Or Steel Comp 4140 Or Steel Comp 4037
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Mil-s-6098 Mil Spec 3rd Material Response Or Mil-s-8503 Mil Spec 4th Material Response Or Mil-s-5626 Mil Spec 5th Material Response Or Ams 6300 Assn Std 6th Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS623-3-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.