



Military-Fasteners.com

P/N NAS623-5-14

Description

NAS623-5-14 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS623514
Minimum Qty (MOQ):	10
NSN:	5305-00-373-0129
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS623-5-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.350 Inches Minimum And 0.400 Inches Maximum
Fastener Length:	1.235 Inches Minimum And 1.265 Inches Maximum
Head Style:	Pan
Head Diameter:	0.594 Inches Minimum And 0.651 Inches Maximum
Head Height:	0.203 Inches Minimum And 0.218 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas623 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS623-5-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.