

P/N NAS624-18

Description

twelve point, external wrenching

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS62418

Minimum Qty (MOQ): 10

NSN: 5306-00-269-4454

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS624-18 Specifications

Thread Class: 3a	
Thread Direction: Rig	ght-hand
Thread Length: 0.4	460 Inches Minimum And 0.510 Inches Maximum
Fastener Length: 1.5	595 Inches Minimum And 1.625 Inches Maximum
Head Style: Doo	ouble Hexagon W/hole
Head Height: 0.3	300 Inches Nominal
Width Between Flats: 0.3	306 Inches Minimum And 0.315 Inches Maximum
Extended Washer Diameter: 0.4	433 Inches Nominal
Extended Washer Thickness: 0.0	069 Inches Nominal
Grip Diameter: 0.2	2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter: 0.2	250 Inches
Grip Length: 1.1	115 Inches Minimum And 1.135 Inches Maximum
Thread Quantity Per Inch: 28	3
Minimum Tensile Strength: 180	30000 Pounds Per Square Inch
Hardness Rating: 39.	9.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material: Ste	eel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
Surface Treatment: Cad	admium Overall
Thread Series Designator: Unf	nf
Specification/standard Data: 802	0205-nas624 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS624-18 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.