



★ FASTENERS

Military-Fasteners.com

P/N NAS624-18

Description

twelve point, external wrenching

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS62418
Minimum Qty (MOQ):	10
NSN:	5306-00-269-4454
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS624-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.460 Inches Minimum And 0.510 Inches Maximum
Fastener Length:	1.595 Inches Minimum And 1.625 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.300 Inches Nominal
Width Between Flats:	0.306 Inches Minimum And 0.315 Inches Maximum
Extended Washer Diameter:	0.433 Inches Nominal
Extended Washer Thickness:	0.069 Inches Nominal
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas624 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS624-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.