

**Description**

length: 1.110", grip: 0.625", thread: 1/4-28, twelve point external wrenching bolt, drilled head, cadmium plated steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS624H10
Minimum Qty (MOQ):	5
NSN:	5306-00-808-7274
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS624H10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.460 Inches Minimum And 0.510 Inches Maximum
<b>Fastener Length:</b>	1.095 Inches Minimum And 1.125 Inches Maximum
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.290 Inches Minimum And 0.310 Inches Maximum
<b>Width Between Flats:</b>	0.306 Inches Minimum And 0.315 Inches Maximum
<b>Extended Washer Diameter:</b>	0.428 Inches Minimum And 0.438 Inches Maximum
<b>Extended Washer Thickness:</b>	0.059 Inches Minimum And 0.079 Inches Maximum
<b>Hole Diameter:</b>	0.032 Inches Minimum And 0.042 Inches Maximum
<b>Grip Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Hole Quantity:</b>	4
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	28
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Hole Configuration Style:</b>	Round Longitudinal Hole
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Nas 672 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas624 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS624H10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.