

## **P/N NAS624H10**

### **Description**

length: 1.110", grip: 0.625", thread: 1/4-28, twelve point external wrenching bolt, drilled head, cadmium plated steel

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS624H10

Minimum Qty (MOQ): 5

NSN: 5306-00-808-7274

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS624H10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.460 Inches Minimum And 0.510 Inches Maximum
Fastener Length:	1.095 Inches Minimum And 1.125 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.290 Inches Minimum And 0.310 Inches Maximum
Width Between Flats:	0.306 Inches Minimum And 0.315 Inches Maximum
Extended Washer Diameter:	0.428 Inches Minimum And 0.438 Inches Maximum
Extended Washer Thickness:	0.059 Inches Minimum And 0.079 Inches Maximum
Hole Diameter:	0.032 Inches Minimum And 0.042 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Hole Configuration Style:	Round Longitudinal Hole
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas624 Professional/industrial Association Standard

## **How to Order**

$Order\ this\ shear\ bolt\ from\ our\ inventory\ online\ by\ visiting\ \underline{https://military-fasteners.com/bolts/shear+bolts/NAS624H10}\ and\ selecting\ the\ quantity\ you\ want\ then\ described by\ visiting\ \underline{https://military-fasteners.com/bolts/shear+bolts/NAS624H10}\ and\ selecting\ the\ quantity\ you\ want\ then\ \underline{https://military-fasteners.com/bolts/shear+bolts/NAS624H10}\ and\ selecting\ the\ quantity\ you\ want\ the\ you\ you\ you\ you\ you\ you\ you\ you$
click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.
Provided by Military-Fasteners.com