

P/N NAS626-10

Description

Fastener Length: 1-1/4", Thread: 3/8-24, Thread Length: 41/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS62610
Minimum Qty (MOQ): 5

NSN: 5306-00-680-6309

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



P/N NAS626-10 Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.594 Inches Minimum And 0.644 Inches Maximum |
| Fastener Length: | 1.229 Inches Minimum And 1.259 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.388 Inches Nominal |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Extended Washer Diameter: | 0.644 Inches Nominal |
| Extended Washer Thickness: | 0.091 Inches Nominal |
| Grip Diameter: | 0.3735 Inches Minimum And 0.3745 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.635 Inches Nominal |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hardness Rating: | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall |
| Material Document And | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd |
| Classification: | Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Nas 672 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas626 Professional/industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS626-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS626-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS626-10 and selecting the quantity you want then click "add to cart".