

Description

Fastener Length: 1-3/8", Thread: 3/8-24, Thread Length: 41/64", twelve point, external wrenching

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS62612
Minimum Qty (MOQ):	10
NSN:	5306-00-680-6308
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS626-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Minimum And 0.644 Inches Maximum
Fastener Length:	1.354 Inches Minimum And 1.384 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.388 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter:	0.644 Inches Nominal
Extended Washer Thickness:	0.091 Inches Nominal
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS626-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.