

# P/N NAS626-12

Military-Fasteners.com

#### Description

Fastener Length: 1-3/8", Thread: 3/8-24, Thread Length: 41/64", twelve point, external wrenching

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | NAS62612                                  |
|-------------------------|---|
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5306-00-680-6308                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS626-12 Specifications

| Thread Class:                                     | За   |
|---|--|
| Thread Direction:                                 | Right-hand   |
| Thread Length:                                    | 0.594 Inches Minimum And 0.644 Inches Maximum  |
| Fastener Length:                                  | 1.354 Inches Minimum And 1.384 Inches Maximum  |
| Head Style:                                       | Double Hexagon W/hole  |
| Head Height:                                      | 0.388 Inches Nominal   |
| Width Between Flats:                              | 0.430 Inches Minimum And 0.439 Inches Maximum  |
| Extended Washer Diameter:                         | 0.644 Inches Nominal   |
| Extended Washer Thickness:                        | 0.091 Inches Nominal   |
| Grip Diameter:                                    | 0.3735 Inches Minimum And 0.3745 Inches Maximum  |
| Nominal Thread Diameter:                          | 0.375 Inches   |
| Grip Length:                                      | 0.740 Inches Minimum And 0.760 Inches Maximum  |
| Thread Quantity Per Inch:                         | 24   |
| Minimum Tensile Strength:                         | 180000 Pounds Per Square Inch  |
| Hardness Rating:                                  | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall  |
| Material:   | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall   |
| Material Document And<br>Classification:          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material<br>Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| Surface Treatment:                                | Cadmium Overall  |
| Surface Treatment Document<br>And Classification: | Nas 672 Assn Std Single Treatment Response Overall   |
| Thread Series Designator:                         | Unf  |

## How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS626-12</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.