

Description

Fastener Length: 2-1/16", Thread: 3/8-24, Thread Length: 11/16", NAS626 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS62623
Minimum Qty (MOQ):	2
NSN:	5306-00-813-8050
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS626-23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.644 Inches Minimum And 0.694 Inches Maximum
Fastener Length:	2.041 Inches Minimum And 2.071 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.388 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter:	0.644 Inches Nominal
Extended Washer Thickness:	0.091 Inches Nominal
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.427 Inches Minimum And 1.447 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas626 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS626-23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.