

P/N NAS626H16

Description

Fastener Length: 1-5/8", Hole Diameter: 3/64", Thread: 3/8-24, Thread Length: 41/64", NAS626 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS626H16

Minimum Qty (MOQ): 5

NSN: 5306-01-305-2567

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS626H16 Specifications

3a
Right-hand
0.594 Inches Minimum And 0.644 Inches Maximum
1.604 Inches Minimum And 1.634 Inches Maximum
Double Hexagon W/hole
0.378 Inches Minimum And 0.398 Inches Maximum
0.430 Inches Minimum And 0.439 Inches Maximum
0.639 Inches Minimum And 0.649 Inches Maximum
0.081 Inches Minimum And 0.101 Inches Maximum
0.050 Inches Minimum And 0.060 Inches Maximum
0.3735 Inches Minimum And 0.3745 Inches Maximum
0.375 Inches
0.990 Inches Minimum And 1.010 Inches Maximum
4
Drilled
24
180000 Pounds Per Square Inch
39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Hexagon Flats
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Threads
Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall
Unjf

How to Order

