

Description

Fastener Length: 13/16", Hole Diameter: 3/64", Thread: 3/8-24, Thread Length: 41/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS626H2 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-889-2933 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS626H2 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.594 Inches Minimum And 0.644 Inches Maximum |
| Fastener Length: | 0.792 Inches Minimum And 0.822 Inches Maximum |
| Head Style: | Double Hexagon Extended Washer |
| Head Height: | 0.378 Inches Minimum And 0.398 Inches Maximum |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Extended Washer Diameter: | 0.639 Inches Minimum And 0.649 Inches Maximum |
| Extended Washer Thickness: | 0.081 Inches Minimum And 0.101 Inches Maximum |
| Hole Diameter: | 0.050 Inches Minimum And 0.060 Inches Maximum |
| Grip Diameter: | 0.3735 Inches Minimum And 0.3745 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hardness Rating: | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Double Hexagon Flats |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas626 Professional/Industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS626H2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.