

**Description**

Fastener Length: 2-13/32", Hole Diameter: ", Thread: 3/8-24,

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS626H29
Minimum Qty (MOQ):	5
NSN:	5306-01-592-3240
ECCN:	EAR99

NO IMAGE  
AVAILABLE

# P/N NAS626H29 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.619 Inches Nominal
<b>Fastener Length:</b>	2.417 Inches Nominal
<b>Head Style:</b>	Spline Extended Washer
<b>Head Height:</b>	0.388 Inches Nominal
<b>Extended Washer Diameter:</b>	0.644 Nominal Inches
<b>Extended Washer Thickness:</b>	0.091 Inches Nominal
<b>Hole Diameter:</b>	0.055 Inches Nominal
<b>Grip Diameter:</b>	0.3735 Nominal Mils And 0.3745 Nominal Centimeters
<b>Head Minor Diameter:</b>	0.438 Nominal Inches
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	1.798 Nominal Inches
<b>Hole Quantity:</b>	4
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Hole Configuration Style:</b>	Double Hexagon Longitudinal Hole
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Ams6382 Assn Std Single Material Response Overall Or Ams6415 Assn Std Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Nas672 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS626H29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.