



Military-Fasteners.com

P/N NAS626H29

Description

Fastener Length: 2-13/32", Hole Diameter: ", Thread: 3/8-24,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS626H29
Minimum Qty (MOQ):	5
NSN:	5306-01-592-3240
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS626H29 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.619 Inches Nominal
Fastener Length:	2.417 Inches Nominal
Head Style:	Spline Extended Washer
Head Height:	0.388 Inches Nominal
Extended Washer Diameter:	0.644 Nominal Inches
Extended Washer Thickness:	0.091 Inches Nominal
Hole Diameter:	0.055 Inches Nominal
Grip Diameter:	0.3735 Nominal Mils And 0.3745 Nominal Centimeters
Head Minor Diameter:	0.438 Nominal Inches
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.798 Nominal Inches
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Ams6382 Assn Std Single Material Response Overall Or Ams6415 Assn Std Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS626H29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.