

**Description**

Fastener Length: 2-13/32", Hole Diameter: ", Thread: 3/8-24,

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS626H29        |
| Minimum Qty (MOQ): | 5                |
| NSN:               | 5306-01-592-3240 |
| ECCN:              | EAR99            |

NO IMAGE  
AVAILABLE

## P/N NAS626H29 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.619 Inches Nominal  |
| <b>Fastener Length:</b>                               | 2.417 Inches Nominal  |
| <b>Head Style:</b>                                    | Spline Extended Washer  |
| <b>Head Height:</b>                                   | 0.388 Inches Nominal  |
| <b>Extended Washer Diameter:</b>                      | 0.644 Nominal Inches  |
| <b>Extended Washer Thickness:</b>                     | 0.091 Inches Nominal  |
| <b>Hole Diameter:</b>                                 | 0.055 Inches Nominal  |
| <b>Grip Diameter:</b>                                 | 0.3735 Nominal Mils And 0.3745 Nominal Centimeters  |
| <b>Head Minor Diameter:</b>                           | 0.438 Nominal Inches  |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches  |
| <b>Grip Length:</b>                                   | 1.798 Nominal Inches  |
| <b>Hole Quantity:</b>                                 | 4   |
| <b>Hole Type:</b>                                     | Drilled   |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 180000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall   |
| <b>Hole Configuration Style:</b>                      | Double Hexagon Longitudinal Hole  |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall   |
| <b>Material Document And Classification:</b>          | Ams6382 Assn Std Single Material Response Overall Or Ams6415 Assn Std Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Nas672 Assn Std Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS626H29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.