

**Description**

Fastener Length: 2-1/2", Hole Diameter: 1-1/4", Thread: 3/8-24, Thread Length: 11/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS626H30                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-01-421-8712                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS626H30 Specifications

|                                     |  |
|-------------------------------------|--|
| <b>Thread Class:</b>                | 3a   |
| <b>Thread Direction:</b>            | Right-hand   |
| <b>Thread Length:</b>               | 0.644 Inches Minimum And 0.694 Inches Maximum  |
| <b>Fastener Length:</b>             | 2.479 Inches Minimum And 2.509 Inches Maximum  |
| <b>Head Style:</b>                  | Double Hexagon W/hole  |
| <b>Head Height:</b>                 | 0.388 Inches Nominal   |
| <b>Width Between Flats:</b>         | 0.430 Inches Minimum And 0.439 Inches Maximum  |
| <b>Extended Washer Diameter:</b>    | 0.644 Inches Nominal   |
| <b>Extended Washer Thickness:</b>   | 0.091 Inches Nominal   |
| <b>Hole Diameter:</b>               | 1.240 Inches Minimum And 1.260 Inches Maximum  |
| <b>Grip Diameter:</b>               | 0.3735 Inches Minimum And 0.3745 Inches Maximum  |
| <b>Nominal Thread Diameter:</b>     | 0.375 Inches   |
| <b>Grip Length:</b>                 | B1.865 Nema Lifting Type K Nominal And 1.885 Inches Maximum  |
| <b>Hole Quantity:</b>               | 4  |
| <b>Hole Type:</b>                   | Drilled  |
| <b>Thread Quantity Per Inch:</b>    | 24   |
| <b>Minimum Tensile Strength:</b>    | 180000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>             | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall  |
| <b>Hole Configuration Style:</b>    | Double Hexagon Longitudinal Hole   |
| <b>Material:</b>                    | Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall |
| <b>Surface Treatment:</b>           | Cadmium Overall  |
| <b>Thread Series Designator:</b>    | Unf  |
| <b>Specification/standard Data:</b> | 80205-nas626 Professional/Industrial Association Standard  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS626H30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.