



Military-Fasteners.com

P/N NAS626H6

## Description

Fastener Length: 0-63/64", Hole Diameter: ", Thread: 3/8-24, Thread Length: 41/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS626H6                                  |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-811-9537                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

# P/N NAS626H6 Specifications

|  |   |
|--|---|
| Thread Class:                                  | 3a  |
| Thread Direction:                              | Right-hand  |
| Thread Length:                                 | 0.594 Inches Minimum And 0.644 Inches Maximum   |
| Fastener Length:                               | 0.979 Inches Minimum And 1.009 Inches Maximum   |
| Head Style:                                    | Double Hexagon W/hole   |
| Head Height:                                   | 0.388 Inches Nominal  |
| Width Between Flats:                           | 0.430 Inches Minimum And 0.439 Inches Maximum   |
| Extended Washer Diameter:                      | 0.644 Inches Nominal  |
| Extended Washer Thickness:                     | 0.091 Inches Nominal  |
| Hole Diameter:                                 | 0.055 Inches Nominal  |
| Grip Diameter:                                 | 0.3735 Inches Minimum And 0.3745 Inches Maximum   |
| Nominal Thread Diameter:                       | 0.375 Inches  |
| Grip Length:                                   | 0.365 Inches Minimum And 0.385 Inches Maximum   |
| Hole Quantity:                                 | 4   |
| Hole Type:                                     | Drilled   |
| Thread Quantity Per Inch:                      | 24  |
| Minimum Tensile Strength:                      | 180000 Pounds Per Square Inch   |
| Hardness Rating:                               | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall   |
| Hole Configuration Style:                      | Double Hexagon Longitudinal Hole  |
| Material:                                      | Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall  |
| Material Document And Classification:          | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall |
| Surface Treatment:                             | Cadmium Overall   |
| Surface Treatment Document And Classification: | Nas 672 Assn Std Single Treatment Response Overall  |
| Thread Series Designator:                      | Unf   |
| Specification/standard Data:                   | 80205-nas626 Professional/industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS626H6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.