

P/N NAS627H10

Description

Thread Qty: 20, Drilled: Head, Material: Steel, Surface Treatment: Cadmium, Tensile Strength: 180000, Head Style: Double Hexagon, NAS627H series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS627H10

Minimum Qty (MOQ):

NSN: 5306-00-574-0369

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS627H10 Specifications

Thread Class:	22
	3a
Thread Direction:	Right-hand
Thread Length:	0.669 Inches Minimum And 0.719 Inches Maximum
Fastener Length:	1.304 Inches Minimum And 1.334 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.425 Inches Minimum And 0.445 Inches Maximum
Width Between Flats:	0.494 Inches Minimum And 0.503 Inches Maximum
Extended Washer Diameter:	0.740 Inches Minimum And 0.750 Inches Maximum
Extended Washer Thickness:	0.089 Inches Minimum And 0.109 Inches Maximum
Hole Diameter:	0.055 Inches Nominal
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas627 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS627H10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.