

Description

Fastener Length: 2-5/64", Thread: 7/16-20, Thread Length: 23/32", NAS627 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS627H22
Minimum Qty (MOQ):	5
NSN:	5306-00-068-0002
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS627H22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.669 Inches Minimum And 0.719 Inches Maximum
Fastener Length:	2.054 Inches Minimum And 2.084 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.425 Inches Minimum And 0.445 Inches Maximum
Width Between Flats:	0.494 Inches Minimum And 0.503 Inches Maximum
Extended Washer Diameter:	0.740 Inches Minimum And 0.750 Inches Maximum
Extended Washer Thickness:	0.089 Inches Minimum And 0.109 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Grip Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas627 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS627H22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.