

## **P/N NAS628H20**

### **Description**

Fastener Length: 1-63/64", Thread: 1/2-20, Thread Length: 49/64

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS628H20

Minimum Qty (MOQ):

NSN: 5306-00-078-5698

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS628H20 Specifications**

Thurs of Classic	n -
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.716 Inches Minimum And 0.766 Inches Maximum
Fastener Length:	1.976 Inches Minimum And 2.006 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.494 Inches Minimum And 0.514 Inches Maximum
Width Between Flats:	0.552 Inches Minimum And 0.572 Inches Maximum
Extended Washer Diameter:	0.818 Inches Minimum And 0.828 Inches Maximum
Extended Washer Thickness:	0.213 Inches Minimum And 0.233 Inches Maximum
Grip Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	43.0 Rockwell C Nominal Overall
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas628 Professional/industrial Association Standard

## **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS628H20">https://military-fasteners.com/bolts/shear+bolts/NAS628H20</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS628H20">https://military-fasteners.com/bolts/shear+bolts/NAS628H20</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS628H20">https://military-fasteners.com/bolts/shear+bolts/NAS628H20</a> and selecting the quantity you want then click "add to cart".