



Military-Fasteners.com

P/N NAS628H28

Description

Fastener Length: 2-31/64", Thread: 1/2-20, Thread Length: 47/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS628H28 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-055-6281 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS628H28 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.741 Inches Nominal |
| Fastener Length: | 2.491 Inches Nominal |
| Head Style: | Double Hexagon Extended Washer |
| Head Height: | 0.504 Inches Nominal |
| Width Between Flats: | 0.556 Inches Minimum And 0.565 Inches Maximum |
| Extended Washer Diameter: | 0.823 Inches Nominal |
| Extended Washer Thickness: | 0.123 Inches Nominal |
| Grip Diameter: | 0.4985 Inches Minimum And 0.4995 Inches Maximum |
| Nominal Thread Diameter: | 0.500 Inches |
| Grip Length: | 1.750 Inches Nominal |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Material: | Steel Comp 8735 Overall |
| Material Document And Classification: | Aisi Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Nas 672 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS628H28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.