



Military-Fasteners.com

P/N NAS628H28

Description

Fastener Length: 2-31/64", Thread: 1/2-20, Thread Length: 47/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS628H28
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-055-6281
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS628H28 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.741 Inches Nominal
Fastener Length:	2.491 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.504 Inches Nominal
Width Between Flats:	0.556 Inches Minimum And 0.565 Inches Maximum
Extended Washer Diameter:	0.823 Inches Nominal
Extended Washer Thickness:	0.123 Inches Nominal
Grip Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.750 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Material:	Steel Comp 8735 Overall
Material Document And Classification:	Aisi Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS628H28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.