

P/N NAS629H6

Description

Fastener Length: 1-3/16", Hole Diameter: ", Thread: 1/2-18, Thread Length: 13/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS629H6

Minimum Qty (MOQ):

NSN: 5306-00-954-6842

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS629H6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.826 Inches Minimum
Fastener Length:	1.201 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.557 Inches Nominal
Width Between Flats:	0.619 Inches Minimum And 0.628 Inches Maximum
Extended Washer Diameter:	0.933 Inches Nominal
Extended Washer Thickness:	0.133 Inches Nominal
Hole Diameter:	0.055 Inches Nominal
Grip Diameter:	0.5605 Inches Minimum And 0.5615 Inches Maximum
Nominal Thread Diameter:	0.562 Inches
Grip Length:	0.375 Inches Nominal
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Material:	Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas629 Professional/industrial Association Standard

How to Order

