

P/N NAS630-22

Description

Fastener Length: 2-1/4", Thread: 5/8-18, Thread Length: 57/64

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS63022

Minimum Qty (MOQ):

NSN: 5306-00-727-9650

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS630-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.848 Inches Minimum And 0.898 Inches Maximum
Fastener Length:	2.233 Inches Minimum And 2.263 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.618 Inches Nominal
Width Between Flats:	0.682 Inches Minimum And 0.691 Inches Maximum
Extended Washer Diameter:	1.045 Inches Nominal
Extended Washer Thickness:	0.150 Inches Nominal
Grip Diameter:	0.6230 Inches Minimum And 0.6240 Inches Maximum
Nominal Thread Diameter:	0.625 Inches
Grip Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Material:	Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas630 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS630-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS630-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS630-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS630-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/naseners.com