

Description

Fastener Length: 6-63/64", Thread: 5/8-18, Thread Length: 57/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS63098 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-816-2408 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS630-98 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.848 Inches Minimum And 0.898 Inches Maximum |
| Fastener Length: | 6.983 Inches Minimum And 7.013 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.608 Inches Minimum And 0.628 Inches Maximum |
| Width Between Flats: | 0.682 Inches Minimum And 0.691 Inches Maximum |
| Extended Washer Diameter: | 1.040 Inches Minimum And 1.050 Inches Maximum |
| Extended Washer Thickness: | 0.140 Inches Minimum And 0.160 Inches Maximum |
| Grip Diameter: | 0.6230 Inches Minimum And 0.6240 Inches Maximum |
| Nominal Thread Diameter: | 0.625 Inches |
| Grip Length: | 6.115 Inches Minimum And 6.125 Inches Maximum |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hardness Rating: | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Material: | Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall Or Steel Comp 4140 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Nas 672 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas630 Professional/Industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS630-98> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.