



Military-Fasteners.com

P/N NAS6303-15D

Description

Fastener Length: 1-17/64", Thread: 10-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS630315D                                |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-01-396-8003                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS6303-15D Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.325 Inches Nominal  |
| <b>Fastener Length:</b>   | 1.246 Inches Minimum And 1.276 Inches Maximum                       |
| <b>Head Style:</b>  | Dished Hexagon  |
| <b>Head Height:</b>   | 0.110 Inches Minimum And 0.125 Inches Maximum                       |
| <b>Width Between Flats:</b>   | 0.367 Inches Minimum And 0.376 Inches Maximum                       |
| <b>Grip Diameter:</b>   | 0.1885 Inches Minimum And 0.1895 Inches Maximum                     |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole |
| <b>Nominal Thread Diameter:</b>   | 0.190 Inches  |
| <b>Grip Length:</b>   | 0.865 Inches Minimum And 0.885 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>  | 32  |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch                                       |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 1.092 Inches Minimum First Hole And 1.102 Inches Maximum First Hole |
| <b>Material:</b>  | Iron Alloy 660 Overall  |
| <b>Surface Treatment:</b>   | Cadmium Overall And Chromate Overall                                |
| <b>Thread Series Designator:</b>  | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6303-15D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.