

Description

Fastener Length: 1-17/64", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS630315D
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-396-8003
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6303-15D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.325 Inches Nominal
Fastener Length:	1.246 Inches Minimum And 1.276 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.092 Inches Minimum First Hole And 1.102 Inches Maximum First Hole
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6303-15D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.